

## C HOOK for handling of coils

### TECHNICAL CHARACTERISTICS

- For all type of coil dimensions and weights
- Minimum loss of height
- Robust steel structure with high elastic limit
- Hanger for easy manoeuvring the "C" hook

### OPTIONALS:

- Implementation of weighing system with accuracy del 0,1%.
  - Upper protection for avoiding damages to coil (teflon)
  - Storage chair for "C" hook
  - Safety clip
- Reduced design to be used in uncoiler



### DATA TO ASK FOR OFFER:

- Max Coil weight= \_\_\_\_\_
- Working group FEM/DIN: \_\_\_\_\_
- Crane hook number= \_\_\_\_\_

### Required dimensions of coils

- Coil max length [ $H_{M\acute{a}x.}$ : \_\_\_\_\_]
- Coil min length [ $H_{m\acute{i}n.}$ : \_\_\_\_\_]
- Coil max. inner  $\varnothing$  [ $\varnothing G_{M\acute{a}x.}$ : \_\_\_\_\_]
- Coil min. inner  $\varnothing$ . [ $\varnothing G_{m\acute{i}n.}$ : \_\_\_\_\_]
- Coil max. outer  $\varnothing$ . [ $\varnothing F_{M\acute{a}x.}$ : \_\_\_\_\_]
- Coil min. outer  $\varnothing$ . [ $\varnothing F_{m\acute{i}n.}$ : \_\_\_\_\_]

### Necessary reduced dimensions:

- Width [I: \_\_\_\_\_]
- Height [J: \_\_\_\_\_]

